


The SecPropGRAPH program

The SecPropGRAPH program computes the geometric properties of thin-walled open cross-sections. It was written and tested in MATLAB 7.3.0 (R2006b). The program is a function with the syntax:

```
Section = SecPropGRAPH( Vertices , Edges )
```

where:

Vertices – array containing the consecutive vertex numbers and their coordinates (y, z),
Edges – array containing the consecutive edge numbers and their thicknesses,
Section – output structure.



Rys. 1. Graph

Example script:

```
Vertices = [  
    1 -0.04  0  
    2 -0.03  0  
    3 -0.02  0  
    ...  
   17 -0.02  0.1  
];  
  
Edges = [  
    1  1  2  0.005  
    2  2  3  0.005  
    3  3  4  0.005
```

```

...
16 16 17 0.005
];
Section = SecPropGRAPH(Vertices, Edges)

```

As a result, the program returns the Section structure:

```

Area: 8.0000e-004
Sy: 9.7409e-021
Sz: -2.3293e-021
So: 9.9262e-023
Jy: 1.1487e-006
Jz: 7.5446e-008
Jyz: -1.4426e-021
Jr: 1.2242e-006
Jt: 6.6667e-009
Jo: 7.0940e-011
Jyo: -2.1403e-023
Jzo: -9.9262e-023
Jry: -5.9613e-009
Jrz: 5.9252e-009
Jro: -3.7094e-011
UserYc: -0.0062
UserZc: 0.0437
UserYs: 0.0067
UserZs: 0.0170
UserYq: -0.0162
UserZq: 6.9389e-018
Ys: 0.0159
Zs: -0.0252
Yq: -0.0050
Zq: -0.0446
Gamma: -0.1116
Transform: [2x2 double]
Vertices: [17x4 double]

```

The following notation is used in the formulas below:

d – dendrite (tree-like graph) of the cross-section midline,

s – path parameter along the directed midline,

$t(s)$ – edge thickness,

$h(s)$ – edge length,

$\omega(s)$ – sectorial coordinate,

$y(s), z(s)$ – parametric coordinates of the cross-section midline.

The output structure Section contains the following fields:

Area – cross-sectional area of the thin-walled profile,

$$A = \int_d t(s) \, ds, \quad (1)$$

S_y – first moment of area about the y axis,

$$S_y = \int_d z(s) \cdot t(s) \, ds, \quad (2)$$

Sz – first moment of area about the z axis,

$$S_z = \int_d y(s) \cdot t(s) \, ds, \quad (3)$$

So – sectorial first moment of area,

$$S_\omega = \int_d \omega(s) \cdot t(s) \, ds, \quad (4)$$

Jy – second moment of area about the y axis,

$$J_y = \int_d z^2(s) \cdot t(s) \, ds, \quad (5)$$

Jz – second moment of area about the z axis,

$$J_z = \int_d y^2(s) \cdot t(s) \, ds, \quad (6)$$

Jyz – product of inertia,

$$J_{yz} = \int_d y(s) \cdot z(s) \cdot t(s) \, ds, \quad (7)$$

Jr – polar moment of inertia,

$$J_r = \int_d \left(y^2(s) + z^2(s) \right) \cdot t(s) \, ds, \quad (8)$$

Jt – torsion constant,

$$J_t = \frac{1}{3} \sum_{i=1}^n t_i^3 \cdot h_i, \quad (9)$$

Jo – sectorial moment of inertia (warping constant),

$$J_\omega = \int_d \omega^2(s) \cdot t(s) \, ds, \quad (10)$$

Jy ω – sectorial product of inertia,

$$J_{y\omega} = \int_d y(s) \cdot \omega(s) \cdot t(s) \, ds, \quad (11)$$

Jzo – sectorial product of inertia,

$$J_{z\omega} = \int_d z(s) \cdot \omega(s) \cdot t(s) \, ds, \quad (12)$$

Jry – higher-order moment,

$$J_{ry} = \int_d \left(y^2(s) + z^2(s) \right) \cdot y(s) \cdot t(s) \, ds, \quad (13)$$

Jrz – higher-order moment,

$$J_{rz} = \int_d \left(y^2(s) + z^2(s) \right) \cdot z(s) \cdot t(s) \, ds, \quad (14)$$

J_{ro} – higher-order moment,

$$J_{r\omega} = \int_d \left(y^2(s) + z^2(s) \right) \cdot \omega(s) \cdot t(s) \, ds, \quad (15)$$

UserYc, UserZc – coordinates (y_C, z_C) of the centroid in the user coordinate system,

UserYs, UserZs – coordinates (y_S, z_S) of the shear centre in the user coordinate system,

UserYq, UserZq – coordinates (y_Q, z_Q) of the principal point of zero sectorial coordinate in the user coordinate system,


Ys, Zs – coordinates (Y_S, Z_S) of the shear centre in the principal centroidal axes,

Yq, Zq – coordinates (Y_Q, Z_Q) of the principal point of zero sectorial coordinate in the principal centroidal axes,

Gamma – angle γ of the transformation from the local (user-defined) coordinate system to the principal centroidal axes,

Transform – transformation matrix from the local user coordinate system to the principal centroidal axes,

Vertices – vertex coordinates in the principal centroidal axes.



Rys. 2. The SecPropGRAPH program window

The top toolbar contains the following tools:

- | | | |
|--------|---|---|
| Zoom | – | zooming the section sketch in and out, |
| Rotate | – | free rotation of the sketch, |
| Roll | – | rotation of the sketch in the screen plane, |
| Pan | – | panning the sketch, |

- | | |
|------------------------------------|---|
| ☐ User | – view in the user coordinate system, |
| ☐ Principal | – view in the principal centroidal coordinate system, |
| ☐ Edges | – display of vertex numbers, |
| ☐ Vertices | – display of edge numbers. |